

## MATERIAL SAFETY DATA SHEET

### R-134A

Issue Date: 2<sup>nd</sup> May 2020

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<b>PRODUCT NAME:</b>	R-134A
<b>MATERIAL CAS NUMBER:</b>	811-97-2
<b>FORMULA:</b>	CH <sub>2</sub> FCF <sub>3</sub>
<b>MOLECULAR WEIGHT:</b>	102.0
<b>TRADENAMES AND SYNONYMS:</b>	HFC-134a, Tetrafluoroethane, R-134a
<b>SUPPLIER:</b>	Dynaflor Co. Ltd., Nana Bhai Lane Fort, Mumbai - 400 001, India

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS #	WEIGHT %	COMMON NAME
ETHANE, 1,1,1,2 -TETRAFLUORO	811-97-2	100%	HFC-134A

#### 3. HAZARDS IDENTIFICATION



H280:	Contains gas under pressure; may explode if heated.
EUH018:	In use may form flammable/explosive vapour- air mixture.
EUH044:	Risk of explosion if heated under confinement.

**SKIN CONTACT:** Immediate effects of overexposure may include: Frostbite, if liquid or escaping vapor contacts the skin.

**EYE CONTACT:** "Frostbite-like" effects may occur if the liquid or escaping vapors contact the eyes.



# R-134A

---

## **ADDITIONAL HEALTH EFFECTS:**

Increased susceptibility to the effects of this material may be observed in persons with pre-existing disease of the: central nervous system, cardiovascular system.

## **CARCINOGENICITY INFORMATION:**

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

## **4. FIRST AID MEASURES**

### **INHALATION:**

If high concentrations are inhaled, immediately remove to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

### **SKIN CONTACT:**

In case of contact, immediately flush skin with plenty of water for at least 15 minutes, while removing contaminated clothing and shoes. Call a physician. Wash contaminated clothing before reuse. Treat for frostbite if necessary by gently warming affected area.

### **EYE CONTACT:**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

### **INGESTION:**

Ingestion is not considered a potential route of exposure.

### **NOTES TO PHYSICIANS:**

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should only be used with special caution in situations of emergency life support.

## R-134A

### 5. FIRE FIGHTING MEASURES

#### FLAMMABLE PROPERTIES:

<b>FLASH POINT:</b>	No flash point
<b>FLAMMABLE LIMITS IN AIR, % BY VOLUME:</b>	LEL: None per ASTM E681 UEL: None per ASTM E681
<b>AUTOIGNITION:</b>	>743°C(>1369°F)

#### FIRE AND EXPLOSION HAZARDS:

Cylinders may rupture under fire conditions. Decomposition may occur. Contact of welding or soldering torch flame with high concentrations of refrigerant can result in visible changes in the size and color of torch flames. This flame effect will only occur in concentrations of product well above the recommended exposure limit, therefore stop all work and ventilate to disperse refrigerant vapors from the work area before using any open flames. R-134a is not flammable in air at temperatures up to 100°C (212°F) at atmospheric pressure. However, mixtures of R-134a with high concentrations of air at elevated pressure and/or temperature can become combustible in the presence of an ignition source. R-134a can also become combustible in an oxygen enriched environment (oxygen concentrations greater than that in air). Whether a mixture containing R-134a and air, or R-134a in an oxygen enriched atmosphere become combustible depends on the inter-relationship of 1) the temperature 2) the pressure, and 3) the proportion of oxygen in the mixture. In general, R-134a should not be allowed to exist with air above atmospheric pressure or at high temperatures; or in an oxygen enriched environment.

For example, R-134a should NOT be mixed with air under pressure for leak testing or other purposes. Experimental data have also been reported which indicate combustibility of R-134a in the presence of certain concentrations of chlorine.

#### EXTINGUISHING MEDIA:

Use media appropriate for surrounding material.

#### FIRE FIGHTING INSTRUCTIONS:

Cool tank/container with water spray. Self-contained breathing apparatus (SCBA) may be required if cylinders rupture or release under fire conditions. Water runoff should be contained and neutralized prior to release.



# R-134A

## 6. ACCIDENTAL RELEASE MEASURES

### SAFEGUARDS (PERSONNEL):

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Ventilate area, especially low or enclosed places where heavy vapors might collect. Remove open flames. Use self-contained breathing apparatus (SCBA) if large spill or leak occurs.

## 7. HANDLING AND STORAGE

### HANDLING (PERSONNEL):

Use with sufficient ventilation to keep employee exposure below recommended limits.

### HANDLING (PHYSICAL ASPECTS):

R-134a should not be mixed with air for leak testing or used for any other purpose above atmospheric pressure. See Flammable Properties section. Contact with chlorine or other strong oxidizing agents should also be avoided.

**STORAGE:** Store in a clean, dry place. Do not heat above 52°C (126°F).

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### ENGINEERING CONTROLS:

Normal ventilation for standard manufacturing procedures is generally adequate. Local exhaust should be used when large amounts are released. Mechanical ventilation should be used in low or enclosed places. Refrigerant concentration monitors may be necessary to determine vapor concentrations in work areas prior to use of torches or other open flames, or if employees are entering enclosed areas.

### PERSONAL PROTECTIVE EQUIPMENT:

Impervious gloves and chemical splash goggles should be used when handling liquid. Under normal manufacturing conditions, no respiratory protection is required when using this product. Self-contained breathing apparatus (SCBA) is required if a large release occurs.



# R-134A

<b>EXPOSURE GUIDELINES:</b>	Exposure Limits "Aspen" R-134a
<b>PEL (OSHA):</b>	None Established
<b>TLV (ACGIH):</b>	None Established
<b>WEEL (AIHA):</b>	1000 ppm, 8 Hr. TWA

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### PHYSICAL DATA:

<b>BOILING POINT:</b>	26.5°C (-15.7°F) @ 736 mm Hg
<b>VAPOR PRESSURE:</b>	96 psia @ 25°C (77°F)
<b>Vapor Density:</b>	3.6 (Air=1.0) @ 25°C (77°F)
<b>% VOLATILES:</b>	100 WT%
<b>SOLUBILITY IN WATER:</b>	0.15 WT% @ 25°C (77°F) @ 14.7 psia
<b>ODOR:</b>	Ether (slight).
<b>FORM:</b>	Liquefied Gas.
<b>COLOR:</b>	Colorless.
<b>LIQUID DENSITY:</b>	1.21 g/cm <sup>3</sup> @ 25°C (77°F)
<b>SPECIFIC GRAVITY:</b>	1.208 @ 25°C (77°F)
<b>EVAPORATION RATE:</b>	(CCL4 = 1); greater than 1

## 10. STABILITY AND REACTIVITY

<b>CHEMICAL STABILITY:</b>	Stable.
<b>CONDITIONS TO AVOID:</b>	Avoid open flames and high temperatures. Incompatibility with Other Materials. Incompatible with alkali or alkaline earth metals - powdered Al, Zn, Be, etc.
<b>DECOMPOSITION:</b>	Decomposition products are hazardous. This material can be decomposed by high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and possibly carbonyl fluoride. These materials are toxic and irritating. Contact should be avoided.
<b>POLYMERIZATION:</b>	Polymerization will not occur.

## R-134A

### 11. TOXICOLOGICAL INFORMATION

#### ANIMAL DATA:

- EYE:** A short duration spray of vapor produced very slight eye irritation.
- SKIN:** Animal testing indicates this material is a slight skin irritant, but not a skin sensitizer.
- INHALATION:** 4 hours, ALC, rat: 567,000 ppm. Single exposure caused: Cardiac sensitization, a potentially fatal disturbance of heart rhythm associated with a heightened sensitivity to the action of epinephrine. Lowest-Observed-Adverse-Effect-Level for cardiac sensitization: 75,000 ppm. Single exposure caused: Lethargy. Narcosis. Increased respiratory rates. These effects were temporary. Single exposure to near lethal doses caused: Pulmonary edema. Repeated exposure caused: Increased adrenals, liver, spleen weight. Decreased uterine, prostate weight. Repeated dosing of higher concentrations caused: the following temporary effects -Tremors. Incoordination.

#### CARCINOGENIC, DEVELOPMENTAL, REPRODUCTIVE, MUTAGENIC EFFECTS:

In a two-year inhalation study, R-134a, at a concentration of 50,000 ppm, produced an increase in late-occurring benign testicular tumors, testicular hyperplasia and testicular weight. The no-effect-level for this study was 10,000 ppm. Animal data show slight fetotoxicity but only at exposure levels producing other toxic effects in the adult animal. Reproductive data on male mice show: No change in reproductive performance. Tests have shown that this material does not cause genetic damage in bacterial or mammalian cell cultures, or in animals. In animal testing, this material has not caused permanent genetic damage in reproductive cells of mammals (has not produced heritable genetic damage).

### 12. ECOLOGICAL INFORMATION

#### ECOTOXICOLOGICAL INFORMATION:

- AQUATIC TOXICITY:** 48 hour EC50  
Daphnia magna: 980 mg/L. 96 hour LC50  
Rainbow trout: 450 mg/L

## R-134A

### 13. DISPOSAL CONSIDERATIONS

#### WASTE DISPOSAL:

Contaminated R-134a can be recovered by distillation or removed to a permitted waste disposal facility. Comply with Federal, State, and local regulations.

### 14. TRANSPORTATION INFORMATION



#### SHIPPING INFORMATION:

<b>PROPER SHIPPING NAME:</b>	Ethane, 1,1,1,2-Tetrafluoro
<b>HAZARD CLASS:</b>	2.2
<b>UN NO:</b>	3159
<b>DOT/IMO LABEL:</b>	Non-flammable Gas
<b>SHIPPING CONTAINERS:</b>	Cylinders, Tank Cars, Tank Trucks, and Ton Tanks.

### 15. REGULATORY INFORMATION

#### U.S. FEDERAL REGULATIONS:

**TSCA INVENTORY STATUS:** Reported/Included.

#### TITLE III HAZARD CLASSIFICATIONS SECTIONS 311, 312

<b>ACUTE:</b>	Yes
<b>CHRONIC:</b>	Yes
<b>FIRE:</b>	No
<b>REACTIVITY:</b>	No
<b>PRESSURE:</b>	Yes

#### HAZARDOUS CHEMICAL LISTS

<b>SARA EXTREMELY HAZARDOUS SUBSTANCE:</b>	No
<b>CERCLA HAZARDOUS SUBSTANCE:</b>	No
<b>SARA TOXIC CHEMICAL:</b>	No



# R-134A

## 16. OTHER INFORMATIONS

### NFPA, NPCA-HMIS:

#### NPCA-HMIS RATING

<b>HEALTH:</b>	1
<b>FLAMMABILITY:</b>	0
<b>REACTIVITY:</b>	1
<b>PERSONAL PROTECTION:</b>	Rating to be supplied by user depending on use conditions.

### ADDITIONAL INFORMATION:

#### MEDICAL USE:

<b>CAUTION:</b>	Do not use in medical applications involving permanent implantation in the human body.
-----------------	--

## 17. DISCLAIMER

The information recommendations and suggestions herein were compiled from reference material and sources believed to be reliable. This MSDS is not intended as a license to operate under or recommendation to infringe on any patents. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Data contained is based on a worst case condition of one of the constituents used in the refrigerant.